



MATERIAL SAFETY DATA SHEET - MSDS

RAPID SET® LOW-P CEMENT

Date Issued: 5-Oct-2009

SECTION 1 – PRODUCT AND COMPANY INFORMATION

<p>Supplier CTS Cement Manufacturing Corp. 11065 Knott Ave., Suite A Cypress, CA 90630, United States Telephone Number: 714-379-8260 FAX Number: 714-379-8270 Email: info@ctscement.com Website: www.ctscement.com</p>	<p>Manufacturer CTS Cement Manufacturing Corp. 11065 Knott Ave., Suite A Cypress, CA 90630, United States Telephone Number: 714-379-8260 FAX Number: 714-379-8270 Email: info@ctscement.com Website: www.ctscement.com</p>	<table border="1"> <tr><td>Health</td><td>1</td></tr> <tr><td>Fire</td><td>0</td></tr> <tr><td>Reactivity</td><td>0</td></tr> <tr><td>Personal Protection</td><td>E</td></tr> </table>	Health	1	Fire	0	Reactivity	0	Personal Protection	E
Health	1									
Fire	0									
Reactivity	0									
Personal Protection	E									
<p>Supplier Emergency Contact 1-714-379-8260</p>	<p>Manufacturer Emergency Contact 1-714-379-8260</p>									
<p>Product Name: Rapid Set Low-P Cement CAS Number: N/A Chemical Family: Cementitious Powder</p>	<p>MSDS Number: ***** Product Code: ***</p>									

SECTION 2 – COMPONENT INFORMATION

Ingredient (Specific Chemical Identity, Common Name)	CAS Number	% of Total Weight
Calcium Sulfoaluminate Cement	960375-09-1	80-98
Sodium Sulfate	7757-82-6	0-2
Methanal	50-00-0	0-0.1

SECTION 3 – HAZARDOUS INFORMATION

Primary Route(s) of Entry:	Inhalation, Skin, Eye, Ingestion
Inhalation Hazards:	May cause respiratory tract, nose, throat, and lung irritation and inflammation. Long term respiratory exposure may produce silicosis in susceptible persons.
Skin Hazards:	May irritate skin causing drying, redness, rash, and blistering. When mixed with water, a high alkali material is produced which can cause severe skin burns. Individuals may develop allergic dermatitis.
Eye Hazards:	May severely irritate eyes. May develop inflammation of the cornea.
Ingestion Hazards:	May be caustic to mucus tissue.
Chronic Exposure:	Individuals may develop allergic dermatitis, inflammation of the cornea, and inflammation of the nose, throat, and lungs. May cause carcinogenic effects.
Carcinogenic Effects:	May contain crystalline silica, a known Human Carcinogen (Group 1), that can cause silicosis and cancer. Exposure to crystalline silica may also increase the risk of Scleroderma, tuberculosis, and kidney disorders. May contain traces of chemicals on the California Proposition 65 list.

SECTION 4 – FIRST AID INFORMATION

Inhalation:	Remove the individual to fresh air. If irritation persists, get medical attention.
--------------------	--



Skin:	Flush with water immediately. If irritation persists, get medical attention immediately.
Eye:	Flush eyes with plenty of water. If irritation persists, get medical attention immediately.
Ingestion:	If conscious, drink plenty of water, Do not induce vomiting. Get immediate medical attention.

SECTION 5 — PHYSICAL & CHEMICAL PROPERTIES

Boiling Point: >2700°F	Specific Gravity: 2.4 to 2.9	Melting Point: >2700°F
	Vapor Density (AIR = 1): None	Evaporation Rate: None

Appearance and Odor : Light Beige. Odor N/A

SECTION 6 — FIRE & EXPLOSION PROPERTIES

Flash Point : Non-Combustible	Flammable Limits: N/A	LEL: N/A	UEL: N/A
Extinguishing Media: N/A	Special Fire Fighting Procedures: None		

SECTION 7 — REACTIVITY INFORMATION

Stability: Stable	Conditions to Avoid: Unintended contact with water
--------------------------	---

Hazardous Polymerization: Will not occur

Hazardous Decomposition or Byproducts: Silica mixed with hydrofluoric acid may produce a corrosive gas.

Incompatible Materials: When mixed with water, may be highly alkali. Incompatible with acids, ammonium and salts. Avoid contact of silica with powerful oxidizing agents and acids.

SECTION 8 — ACCIDENTAL RELEASE MEASURES

Use a dust free method to clean up spills. Use the appropriate personal protective equipment.

SECTION 9 — HANDLING AND STORAGE

Waste Disposal Method: Use appropriate disposal facility complying with local regulations. Not classified as hazardous waste under RCRA or CERCLA. Do not create dust.

Handling and Storage Precautions: Use proper personal protective equipment. Do not breath dust. Avoid contact with eyes, skin, and clothing. Avoid unintentional contact with water.

SECTION 10 — EXPOSURE CONTROL MEASURES

Engineering Controls: Use with adequate ventilation to control airborne dust levels

Eye Protection: Safety glasses with side shields or goggles are recommended

Skin Protection: Impervious gloves, boots and clothing are recommended to protect the skin from contact

Respiratory Protection: Use a MSHA, OSHA or NIOSH approved respirator.

Hygienic Practices: After handling, thoroughly wash hands and exposed skin with soap and water.

Exposure Limits: Not Available

SECTION 11 — TOXICOLOGY INFORMATION

Toxicity to Animals: LD50 and LC50 rating not determined. A high pH material is produced when mixed with water.



Chronic Effects on Humans: May contain Silica sand, a known carcinogen. May aggravate eye, skin, and respiratory conditions. May contain chemicals on the Proposition 65 list.

SECTION 12 — ECOLOGICAL INFORMATION

No Data Available

SECTION 13 — DISPOSAL CONSIDERATIONS

Not classified as hazardous waste under the Resource Conservation and Recovery Act and the Comprehensive Environmental Response, Compensation, and Recovery Act

SECTION 14 — TRANSPORTATION INFORMATION

Not determined to be hazardous under the U.S. Department of Transportation. Not Regulated by DOT.

SECTION 15 — OTHER REGULATORY INFORMATION

US OSHA 29CFR 1910.1200: May be considered hazardous and should be included in the employers' hazardous communication program.

SARA Section 313 Notification: Not subject to reporting requirements.

Proposition 65: This product may contain materials on the Proposition 65 list.

SECTION 16 — OTHER INFORMATION

Key/Abbreviations

ACGIH – American Conference of Government Industrial Hygienists

CAS – Chemical Abstract Service.

CERCLA – Comprehensive Environmental Response, Compensation & Liability Act.

DOT – Department of Transportation.

LEL – Lower Exposure Limit.

MSHA – Mine Safety and Health Administration.

N/A – Not Applicable.

NIOSH – National Institute for Occupational Safety and Health.

OSHA – Occupational Safety and Health Administration.

RCRA – Resource Conservation and Recovery Act.

SARA – Superfund Amendments and Reauthorization Act.

UEL – Upper Exposure Limit.

NOTE: CTS Cement Manufacturing Corporation makes no representations as to the completeness or accuracy of the information in this document; and, no guarantee or warranty of any kind, express or implied, is made herein. We are not liable for any consequential, incidental, or special damages arising directly or indirectly from the use of this information.