

TRU SPIKED ROLLER

Specialty Finishing Roller for Self-Leveling Overlays



PRODUCT DATASHEET

DESCRIPTION: The Rapid Set® TRU SPIKED ROLLER is a specialty 24" (61 cm) finishing roller with included frame designed specifically for Rapid Set self-leveling products. It efficiently releases air trapped during mixing, significantly reducing pinholes. The SPIKED ROLLER also improves the uniformity of the finished floor by removing lines left by the gauge rake or smoother. The 1-1/4" (3.2 cm) stainless steel spikes are durable and can be easily cleaned for repeated use.

USES: Use the TRU SPIKED ROLLER with Rapid Set® TRU® Self-Leveling, TRU® Gray Self-Leveling, LevelFlor®, Concrete Leveler®, or any other self-leveling overlayment, underlayment or coating.

ASSEMBLY: Loosen the wing nuts and swing the arms out. Insert the roller into the frame and snug the arms. Hand-tighten wing nuts. Then simply insert any standard threaded extension pole into the frame and the roller is ready for use.

INSTRUCTIONS: Place the self-leveling material using traditional methods. Roll the TRU SPIKED ROLLER in the opposite direction of the gauge rake. One pass down and back is generally all that is required to remove entrapped air. Multiple passes may be necessary if bubbles can be seen forming in the surface. Due to the proximity of the steel spikes, this roller may push coarser aggregate, like that found in TRU PC, toward the substrate making it more difficult to expose when ground. For maximum aggregate exposure in TRU PC, use the TRU PC Spiked Roller. Never use the TRU SPIKED ROLLER after the film has begun forming at the surface.

PACKAGING: The TRU SPIKED ROLLER is available in individual boxes with the frame included. The box dimensions are 25" x 5" x 5" (64 cm x 13 cm x 13 cm).

USER RESPONSIBILITY: Before using CTS products, read current technical data sheets, bulletins, product labels and safety data sheets at www.CTScement.com. It is the user's responsibility to review instructions and warnings for any CTS products prior to use.

LIMITED WARRANTY: CTS CEMENT MANUFACTURING CORP. (CTS) warrants its materials to be of good quality and, at its option, will replace or refund the purchase price of any material proven to be defective within one (1) year from date of purchase. The above remedies shall be the limit of CTS' responsibility. Except for the foregoing, all warranties expressed or implied, including merchantability and fitness for a particular purpose, are excluded. CTS shall not be liable for any consequential, incidental, or special damages arising directly or indirectly from the use of the materials.

OVERVIEW

Highlights:

24" wide finishing roller

1-1/4" long, 1/64" super thin stainless steel spikes

Easily place up to 1/2" deep pours

Minimizes Pinholes: Efficiently releases trapped air with ultra-thin stainless steel spikes

Improves Floor Appearance: Removes rake lines and assists leveling

Manufacturer:

CTS Cement Manufacturing Corp.
12442 Knott St.
Garden Grove, CA 92841
Tel: 800-929-3030 | Fax: 714-379-8270
Web: www.CTScement.com
E-mail: info@CTScement.com



USGBC and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.