

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 1 of 12

Asphalt Resurfacer

SECTION 1: Identification

Product identifier

Product name: Asphalt Resurfacer

Product code: 185320025, 185310050

Recommended use of the product and restriction on use

Relevant identified uses: Industrial Use

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

CTS Cement Manufacturing Corporation

12442 Knott St.

Garden Grove, CA 92841

800-929-3030

Emergency telephone number:

United States

CTS Cement Manufacturing Corporation

800-929-3030 (8am - 5pm)

SECTION 2: Hazard(s) identification

GHS classification:

Skin irritation, category 2

Serious eye damage, category 1

Carcinogenicity, category 1A

Specific target organ toxicity - single exposure, category 3, respiratory tract irritation

Specific target organ toxicity - repeated exposure, category 1

Skin sensitization, category 1

Respiratory sensitization, category 1

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H315 Causes skin irritation

H318 Causes serious eye damage

H350 May cause cancer via inhalation.

H335 May cause respiratory irritation

H372 Causes damage to organs (lungs) through prolonged or repeated exposure via inhalation.

H317 May cause an allergic skin reaction

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 2 of 12

Asphalt Resurfacer

Precautionary statements:

- P264 Wash skin thoroughly after handling
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P271 Use only outdoors or in a well-ventilated area
- P270 Do not eat, drink or smoke when using this product
- P272 Contaminated work clothing must not be allowed out of the workplace
- P284 Wear respiratory protection
- P302+P352 IF ON SKIN: Wash with plenty of soap and water
- P321 Specific treatment (see Sections 4 - 8 of this SDS and any supplemental information on the product label).
- P362 Take off contaminated clothing and wash it before reuse
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 Immediately call a POISON CENTER or doctor/physician.
- P308+P313 IF exposed or concerned: Get medical advice/attention
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention
- P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
- P405 Store locked up
- P403+P233 Store in a well-ventilated place. Keep container tightly closed
- P501 Dispose of contents/container in accordance with all local, regional, state and federal regulations.

Hazards not otherwise classified:

Airborne dust may cause mechanical irritation to eyes, nose, throat, and lungs. Direct contact may result in corneal injury.

Wet product poses the additional risk of causing serious, potentially irreversible damage, to the skin and eyes. The same type of tissue destruction can occur if wet or moist areas of the body are exposed for sufficient duration to dry product.

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 14808-60-7	Silica, crystalline quartz	35-65
CAS number: 960375-09-1	Calcium Sulphoaluminate Cement*	10-25
CAS number: 1317-65-3	Ground Calcium Carbonate	1-10
CAS number: Trade Secret	VAE Polymer	2-10
CAS number: 9003-55-8	Synthetic Rubber	0.1-5
CAS number: 1333-86-4	Carbon Black	<2.5
CAS number: 9006-04-6	Rubber, natural	0.1-5
CAS number: 546-93-0	Magnesium carbonate	<1

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 3 of 12

Asphalt Resurfacer

Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

* Calcium Sulphoaluminate Cement is primarily comprised of calcium compounds with oxides of aluminum, iron, sulfur and silica. Trace amounts of naturally occurring; potentially harmful chemicals might be detected during chemical analysis. Trace constituents may include, but not necessarily limited to, magnesium, potassium, sodium oxides and hexavalent chromium.

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If exposed, seek medical advice/attention.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After eye contact:

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

SKIN CONTACT: Exposure may cause irritation and/or an allergic skin reaction. Symptoms include redness, itching, burning and inflammation. Exposure to wet material may cause severe skin burns and irreversible tissue damage.

EYE CONTACT: Exposure may cause serious eye damage. Symptoms include irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

INHALATION: Exposure may cause allergy, asthma symptoms or breathing difficulties. Symptoms may include cough, chronic phlegm, shortness of breath, wheezing and chest tightness. Symptoms may be delayed. Inhalation of dust may irritate the nose, throat and respiratory tract. Symptoms include cough, sore throat, shortness of breath and inflammation of the mucous membranes lining the respiratory tract.

INGESTION: Ingestion is an improbable route of exposure. Ingestion of wet material would cause corrosive burns to mouth, esophagus and stomach. Symptoms include pain, tissue damage, nausea and vomiting.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 4 of 12

Asphalt Resurfacer

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Exposure to respirable silica may cause cancer and damage to organs. Prolonged and/or repeated exposure to silica-containing dust may cause lung damage and a lung disease called silicosis. Silicosis is a progressive and disabling lung disease that causes pulmonary fibrosis, chronic obstructive pulmonary disorder (COPD) and lung cancer. Silicosis lowers the immune system and makes an individual more susceptible to tuberculosis. Silicosis may also cause renal disease and scleroderma – a disease affecting skin, blood vessels, joints and skeletal muscles. Symptoms of silicosis may include (but are not limited to) shortness of breath, difficulty breathing with or without exertion; coughing; diminished work capacity; diminished chest expansion; reduction of lung volume; right heart enlargement and/or failure. Not all individuals with silicosis will exhibit symptoms of the disease. However, silicosis can be progressive, and symptoms can appear at any time, even years after exposures have ceased.

Immediate medical attention and special treatment

Specific treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.

Exposure to wet material requires prompt medical treatment.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

Specific hazards during fire-fighting:

Thermal decomposition may produce irritating and toxic fumes including carbon oxides, sulfur oxides, silicon oxides and metal oxides.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

Special precautions:

Move containers from area of fire, if safe to do so. Use water spray or fog for cooling exposed containers.

Prevent fire-fighting water from entering environment.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Do not breathe dust. Stay upwind. Do not get on skin, eyes or on clothing. Wear recommended personal protective equipment (see Section 8). Do not walk through spilled material. Wash thoroughly after handling.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up:

Minimize generation of dust. Do not dry sweep or use compressed air for clean-up. Wet dry material and then scrape up wet material and place in a suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 5 of 12

Asphalt Resurfacer

SECTION 7: Handling and storage

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Avoid exposure by obtaining and following special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation when possible. Do not get in eyes or on skin or clothing. Do not breathe dust. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not eat, drink or smoke while handling this product. Wash hands, forearms and face after handling. Keep away from incompatible materials (see Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	Silica, crystalline quartz	14808-60-7	8-Hour TWA-PEL: 0.05 mg/m ³
	Silica, crystalline quartz	14808-60-7	8-Hour TWA-PEL: 0.025 mg/m ³ (Action Level)
	Calcium Sulphoaluminate Cement*	960375-09-1	8-Hour TWA-PEL: 15 mg/m ³ (total dust - PNOR)
	Calcium Sulphoaluminate Cement*	960375-09-1	8-Hour TWA-PEL: 5 mg/m ³ (respirable fraction - PNOR)
	Ground Calcium Carbonate	1317-65-3	8-Hour TWA-PEL: 15 mg/m ³ (total dust)
	Ground Calcium Carbonate	1317-65-3	8-Hour TWA-PEL: 5 mg/m ³ (respirable fraction)
	Carbon Black	1333-86-4	PEL: 3.5 mg/m ³ (Table Z-1)
	Carbon Black	1333-86-4	TWA: 3.5 mg/m ³ (Table Z-1-A)
	Magnesium carbonate	546-93-0	TWA: 15 mg/m ³ (Total dust)
	Magnesium carbonate	546-93-0	TWA: 5 mg/m ³ (Respirable fraction)
ACGIH	Silica, crystalline quartz	14808-60-7	8-Hour TWA: 0.025 mg/m ³ (respirable particulate matter)
	Calcium Sulphoaluminate Cement*	960375-09-1	8-Hour TWA: 1 mg/m ³ (respirable particulate matter containing no asbestos and <1% crystalline silica)
	Ground Calcium Carbonate	1317-65-3	8-Hour TWA: 10 mg/m ³ (inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Ground Calcium Carbonate	1317-65-3	8-Hour TWA: 3 mg/m ³ (respirable particles)
	Carbon Black	1333-86-4	8-Hour TWA: 3 mg/m ³
	Magnesium carbonate	546-93-0	TWA: 10 mg/m ³ (Particulate matter containing no asbestos and < 1% crystalline silica)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 6 of 12

Asphalt Resurfacer

Country (Legal Basis)	Substance	Identifier	Permissible concentration
NIOSH	Silica, crystalline quartz	14808-60-7	REL-TWA: 0.05 mg/m ³ (up to 10 hrs.)
	Silica, crystalline quartz	14808-60-7	IDLH: 50 mg/m ³
	Calcium Sulphoaluminate Cement*	960375-09-1	REL-TWA: 10 mg/m ³ (total - 10 H)
	Calcium Sulphoaluminate Cement*	960375-09-1	REL-TWA: 5 mg/m ³ (respirable - 10 H)
	Ground Calcium Carbonate	1317-65-3	REL-TWA: 10 mg/m ³ (total dust - up to 10 hrs.)
	Ground Calcium Carbonate	1317-65-3	REL-TWA: 5 mg/m ³ (respirable fraction - up to 10 hrs.)
	Carbon Black	1333-86-4	REL: 3.5 mg/m ³ (10 hr)
	Carbon Black	1333-86-4	IDLH: 1750 mg/m ³
	Carbon Black	1333-86-4	REL: 0.1 mg/m ³ ((10hr) (in presence of polycyclic aromatic hydrocarbons))
	Magnesium carbonate	546-93-0	REL: 5 mg/m ³ (Respirable fraction)
	Magnesium carbonate	546-93-0	REL: 10 mg/m ³ (Total dust)
United States(California)	Silica, crystalline quartz	14808-60-7	8-Hour TWA-PEL: 0.05 mg/m ³

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Use local exhaust, mechanical ventilation or additional engineering measures to maintain airborne concentration below any occupational exposure limits. Ensure that Emergency eye wash station and safety shower are in good working order and in the immediate vicinity of any possible exposure.

Personal protection equipment

Eye and face protection:

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical-resistant, impervious gloves, complying with an approved standard should be worn at all times when handling chemical products. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Other skin protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 7 of 12

Asphalt Resurfacer

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

General hygienic measures:

Handle in accordance with good industrial hygiene and safety measures. Wash hands and face after handling chemical products. Wash hands before eating, drinking and smoking. Wash hands at the end of the workday. Appropriate techniques should be applied to remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Solid, Gray powder
Odor	Low
Odor threshold	Not determined or not available.
pH	11-12 when wet
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Not determined or not available.
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	2.7 - 3.1 @ 20 °C
Solubilities	Partially soluble in water
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	2460 °F (1350 °C)
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

VOC	0 g/l when mixed with water
-----	-----------------------------

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 8 of 12

Asphalt Resurfacer

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage. Crystalline silica may react violently with strong oxidizing agents, resulting in a fire/explosion hazard. Silica dissolves in hydrofluoric acid to produce silicon tetrafluoride, a corrosive gas. Wet product is alkaline. As such it is incompatible with acids, ammonium salts and aluminum metal.

Conditions to avoid:

Incompatible materials; Dust generation and accumulation; Unintentional contact with water

Incompatible materials:

Strong oxidizing agents; Hydrofluoric acid
Wet product is alkaline and incompatible with acids, ammonium salts and aluminum metal.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Carbon Black	oral	LD50 Rat: 8000 mg/kg

Skin corrosion/irritation

Assessment:

Causes skin irritation.

Product data:

No data available.

Substance data:

Name	Result
Calcium Sulphoaluminate Cement*	Causes skin irritation.

Serious eye damage/irritation

Assessment:

Causes serious eye damage.

Product data:

No data available.

Substance data:

Name	Result
Calcium Sulphoaluminate Cement*	Causes serious eye damage.

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product data:

No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 9 of 12

Asphalt Resurfacer

Substance data:

Name	Result
Calcium Sulphoaluminate Cement*	May cause an allergic skin reaction.
Rubber, natural	May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carcinogenicity

Assessment:

May cause cancer.

Product data: No data available.

Substance data:

Name	Species	Result
Silica, crystalline quartz	Not applicable	May cause lung cancer via inhalation.
Carbon Black	Not applicable	Suspected of causing cancer by inhalation exposure route.

International Agency for Research on Cancer (IARC):

Name	Classification
Silica, crystalline quartz	Group 1
Synthetic Rubber	Group 3
Carbon Black	Group 2B

National Toxicology Program (NTP):

Name	Classification
Silica, crystalline quartz	Known to be human carcinogens

OSHA Carcinogens:

Ingredient Name	CAS	OSHA Carcinogens Status
Silica, crystalline quartz (respirable)	14808-60-7	Yes

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment:

May cause respiratory irritation.

Product data:

No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 10 of 12

Asphalt Resurfacer

Substance data:

Name	Result
Calcium Sulphoaluminate Cement*	May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Assessment:

Causes damage to organs through prolonged or repeated exposure.

Product data:

No data available.

Substance data:

Name	Result
Silica, crystalline quartz	Causes damage to organs (lungs; kidneys; immune system) through prolonged or repeated exposure via inhalation.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

Inhalation; Skin contact; Eye contact

Symptoms related to the physical, chemical and toxicological characteristics:

Refer to Section 4 of this SDS.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 11 of 12

Asphalt Resurfacer

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory agencies. Dispose of in accordance with all applicable local, regional, state and federal regulations.

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 05.14.2020

Page 12 of 12

Asphalt Resurfacer

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA): All product ingredients are listed or exempt from listing.

Significant New Use Rule (TSCA Section 5): No product ingredients listed.

Export notification under TSCA Section 12(b): No product ingredients listed.

SARA Section 302 extremely hazardous substances: No product ingredients listed.

SARA Section 313 toxic chemicals: No product ingredients listed.

CERCLA: No product ingredients listed.

RCRA: No product ingredients listed.

Section 112(r) of the Clean Air Act (CAA): No product ingredients listed.

Massachusetts Right to Know:

14808-60-7	Silica, crystalline quartz	Listed
960375-09-1	Calcium Sulphoaluminate Cement*	Listed
1317-65-3	Ground Calcium Carbonate	Listed
1333-86-4	Carbon Black	Listed
546-93-0	Magnesium carbonate	Listed

New Jersey Right to Know:

14808-60-7	Silica, crystalline quartz	Listed
960375-09-1	Calcium Sulphoaluminate Cement*	Listed
1317-65-3	Ground Calcium Carbonate	Listed
1333-86-4	Carbon Black	Listed
546-93-0	Magnesium carbonate	Listed

New York Right to Know:

960375-09-1	Calcium Sulphoaluminate Cement*	Listed
-------------	---------------------------------	--------

Pennsylvania Right to Know:

14808-60-7	Silica, crystalline quartz	Listed
960375-09-1	Calcium Sulphoaluminate Cement*	Listed
1317-65-3	Ground Calcium Carbonate	Listed
1333-86-4	Carbon Black	Listed

California Proposition 65:

 **WARNING:** Cancer - www.P65Warnings.ca.gov.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 3-0-0

HMIS: 3*-0-0

Initial preparation date: 05.14.2020

End of Safety Data Sheet