



Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 1 of 12

Skim Floor

SECTION 1: Identification

Product identifier

Product name: Rapid Set Skim Floor

Product code: 150110020

Recommended use of the product and restriction on use

Relevant identified uses: Not determined or not applicable.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

CTS Cement Manufacturing Corporation

12442 Knott St.

Garden Grove, CA 92841

800-929-3030

info@ctscement.com

Emergency telephone number:

United States

CTS Cement Manufacturing Corporation

1-800-929-3030 (8 AM - 5 PM)

SECTION 2: Hazard(s) identification

GHS classification:

Skin irritation, category 2

Serious eye damage, category 1

Specific target organ toxicity - single exposure, category 3, respiratory irritation

Carcinogenicity, category 1A

Specific target organ toxicity - repeated exposure, category 2

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 2 of 12

Skim Floor

H350 May cause cancer.

H373 May cause damage to Lungs through prolonged or repeated exposure by inhalation.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash hands/eyes/mouth/skin/clothing thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention

P310 Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313 If exposed or concerned: Get medical advice/attention

P405 Store locked up.

P403+P233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 960375-09-1	Calcium Sulfoaluminate Cement*	20-50
CAS number: 1317-65-3	Ground Calcium Carbonate	20-50
CAS number: 68131-74-8	Fly Ash	10-25
CAS number: Trade Secret	VAE Polymer	5-20
CAS number: 546-93-0	Magnesium Carbonate	0-7
CAS number: 14808-60-7	Total Silica, crystalline quartz	0-3

Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

*Calcium Sulphoaluminate Cement is primarily comprised of calcium compounds with oxides of aluminum, iron, sulfur and silica. Trace amounts of naturally occurring; potentially harmful chemicals might be detected during chemical analysis. Trace constituents may include, but not necessarily limited to, magnesium, potassium, sodium oxides and hexavalent chromium.

SECTION 4: First aid measures

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 3 of 12

Skim Floor

Description of first aid measures

General notes:

Not determined or not applicable.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention. Get medical advice/attention if you feel unwell. Take precautions to ensure your own safety.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After eye contact:

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

SKIN CONTACT: Exposure may cause irritation. Symptoms include redness, itching, burning and inflammation. Exposure to wet material may cause severe skin burns and irreversible tissue damage.

EYE CONTACT: Exposure may cause serious eye damage. Symptoms include irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

INHALATION: Inhalation of dust may irritate the nose, throat and respiratory tract. Symptoms include cough, sore throat, shortness of breath and inflammation of the mucous membranes lining the respiratory tract.

INGESTION: Ingestion is an improbable route of exposure. Ingestion of wet material would cause corrosive burns to mouth, esophagus and stomach. Symptoms include pain, tissue damage, nausea and vomiting.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Exposure to respirable silica may cause cancer and damage to organs. Prolonged and/or repeated exposure to silica-containing dust may cause lung damage and a lung disease called silicosis. Silicosis is a progressive and disabling lung disease that causes pulmonary fibrosis, chronic obstructive pulmonary disorder (COPD) and lung cancer. Silicosis lowers the immune system and makes an individual more susceptible to tuberculosis. Silicosis may also cause renal disease and scleroderma – a disease affecting skin, blood vessels, joints and skeletal muscles. Symptoms of silicosis may include (but are not limited to) shortness of breath, difficulty breathing with or without exertion; coughing; diminished work capacity; diminished chest expansion; reduction of lung volume; right heart enlargement and/or failure. Not all individuals with silicosis will exhibit symptoms of the disease. However, silicosis can be progressive, and symptoms can appear at any time, even years after exposures have ceased.

Immediate medical attention and special treatment

Specific treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued. Exposure to wet material requires prompt medical treatment.

Notes for the doctor:

Treat symptomatically

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 4 of 12

Skim Floor

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 5 of 12

Skim Floor

Carbon monoxide and carbon dioxide may form upon combustion
Heating causes a rise in pressure, risk of bursting and combustion

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

- Ensure adequate ventilation
- Ensure air handling systems are operational
- Wear protective eye wear, gloves and clothing

Environmental precautions:

- Should not be released into the environment
- Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

- Wear protective eye wear, gloves and clothing
- Sweep or scoop up solid material while minimizing dust generation
- Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

Precautions for safe handling:

- Use only with adequate ventilation.
- Avoid breathing dust.
- Do not eat, drink, smoke or use personal products when handling chemical substances.

Conditions for safe storage, including any incompatibilities:

- Keep container tightly sealed.
- Keep container dry.
- Store in a cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Total Silica, crystalline quartz	14808-60-7	TWA 0.025 mg/m ³ USA. ACGIH
	Calcium Sulphoaluminate Cement *	960375-09-1	8-Hour TWA: 1 mg/m ³ (respirable particulate matter containing no asbestos and <1% crystalline silica)
	Magnesium carbonate	546-93-0	TWA: 10 mg/m ³ (Particulate matter containing no asbestos and < 1% crystalline silica)
	Ground Calcium Carbonate	1317-65-3	8-Hour TWA: 10 mg/m ³ (inhalable particulate matter containing no asbestos and < 1% crystalline silica)
	Ground Calcium Carbonate	1317-65-3	8-Hour TWA: 3 mg/m ³ (respirable particles)
United States (OSHA)	Silica, crystalline quartz	14808-60-7	8-Hour TWA-PEL: 0.05 mg/m ³
	Silica, crystalline quartz	14808-60-7	8-Hour TWA-PEL: 0.025 mg/m ³ (Action Level)
	Calcium Sulphoaluminate Cement*	960375-09-1	8-Hour TWA-PEL: 15 mg/m ³ (total dust – PNOR)
	Calcium Sulphoaluminate Cement*	960375-09-1	8-Hour TWA-PEL: 5 mg/m ³ (respirable fraction – PNOR)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 6 of 12

Skim Floor			
	Magnesium carbonate	546-93-0	TWA: 15 mg/m ³ (Total dust)
	Magnesium carbonate	546-93-0	TWA: 5 mg/m ³ (Respirable fraction)
	Ground Calcium Carbonate	1317-65-3	8-Hour TWA-PEL: 15 mg/m ³ (total dust)
	Ground Calcium Carbonate	1317-65-3	8-Hour TWA-PEL: 5 mg/m ³ (respirable fraction)
NIOSH	Silica, crystalline quartz	14808-60-7	REL-TWA: 0.05 mg/m ³ (up to 10
	Silica, crystalline quartz	14808-60-7	IDLH: 50 mg/m ³
	Calcium Sulphoaluminate Cement *	960375-09-1	REL-TWA: 10 mg/m ³ (total - 10 H)
	Calcium Sulphoaluminate Cement *	960375-09-1	REL-TWA: 5 mg/m ³ (respirable -10 H)
	Magnesium carbonate	546-93-0	REL: 5 mg/m ³ (Respirable fraction)
	Magnesium carbonate	546-93-0	REL: 10 mg/m ³ (Total dust)
	Ground Calcium Carbonate	1317-65-3	REL-TWA: 10 mg/m ³ (total dust – up to 10 hrs.)
	Ground Calcium Carbonate	1317-65-3	REL-TWA: 5 mg/m ³ (respirable fraction – up to 10 hrs.)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Solid; gray powder
Odor	Low
Odor threshold	Not available
pH	11 - 12 when wet
Melting point/freezing point	Not available
Initial boiling point/range	Not applicable

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 7 of 12

Skim Floor	
Flash point (closed cup)	Not available
Evaporation rate	Not applicable
Flammability (solid, gas)	Not available
Upper flammability/explosive limit	Not available
Lower flammability/explosive limit	Not available
Vapor pressure	Not applicable
Vapor density	Not applicable
Density	Not available
Relative density	2.7 - 3.1 at 20°C
Solubilities	Partially soluble
Partition coefficient (n-octanol/water)	Not available
Auto/Self-ignition temperature	Not available
Decomposition temperature	2460°F (1350°C)
Dynamic viscosity	Not applicable
Kinematic viscosity	Not applicable
Explosive properties	Not available
Oxidizing properties	Not available

Other information

VOC (Weight %)	0 g/l when mixed with water
----------------	-----------------------------

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

None known.

Incompatible materials:

Strong oxidizing agent; Hydrofluoric acid.

Wet product is alkaline and incompatible with acids, ammonium salts and aluminum metal.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available

Skin corrosion/irritation

Assessment:

Causes skin irritation

Product data:

No data available.

Substance data:

Name	Result
------	--------

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 8 of 12

Skim Floor

Name	Result
Calcium Sulfoaluminate Cement*	Causes skin irritation.

Serious eye damage/irritation

Assessment:

Causes serious eye damage

Product data:

No data available.

Substance data:

Name	Result
Calcium Sulfoaluminate Cement*	Causes serious eye damage.

Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Calcium Sulfoaluminate Cement*	May cause allergic skin reaction.

Carcinogenicity

Assessment:

May cause cancer

Product data: No data available.

Substance data:

Name	Species	Result
Silica, crystalline quartz (Respirable)	Not applicable	Component may cause cancer.
Total Silica, crystalline quartz		1 - Group 1: Carcinogenic to humans (Quartz)

International Agency for Research on Cancer (IARC):

Name	Classification
Silica, crystalline quartz (Respirable)	Group 1 - Carcinogenic to humans

National Toxicology Program (NTP):

Name	Classification
Silica, crystalline quartz (Respirable)	Known to be human carcinogens

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

No data available

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 9 of 12

Skim Floor

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment:

May cause respiratory irritation

Product data:

No data available.

Substance data:

Name	Result
Calcium Sulfoaluminate Cement*	May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Assessment:

May cause damage to organs through prolonged or repeated exposure

Product data:

No data available.

Substance data:

Name	Result
Silica, crystalline quartz (Respirable)	Causes damage to organs (lungs; kidneys; immune system) through prolonged or repeated exposure via inhalation.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 10 of 12

Skim Floor

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 11 of 12

Skim Floor

Packing group	None
Environmental hazards	None
Special precautions for user	None

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA): All product ingredients are listed or exempt from listing.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 extremely hazardous substances: None of the ingredients are listed. None of the ingredients are listed.

SARA Section 313 toxic chemicals: None of the ingredients are listed.

CERCLA: None of the ingredients are listed.

RCRA: None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

960375-09-1	Calcium Sulfoaluminate Cement *	Listed
14808-60-7	Silica, crystalline quartz (Respirable)	Listed
546-93-0	Magnesium Carbonate	Listed
1317-65-3	Ground Calcium Carbonate	Listed

New Jersey Right to Know:

960375-09-1	Calcium Sulfoaluminate Cement *	Listed
14808-60-7	Silica, crystalline quartz (Respirable)	Listed
546-93-0	Magnesium Carbonate	Listed
1317-65-3	Ground Calcium Carbonate	Listed

New York Right to Know:

960375-09-1	Calcium Sulfoaluminate Cement *	Listed
-------------	---------------------------------	--------

Pennsylvania Right to Know:

960375-09-1	Calcium Sulfoaluminate Cement *	Listed
14808-60-7	Silica, crystalline quartz (Respirable)	Listed
1317-65-3	Ground Calcium Carbonate	Listed

California Proposition 65:

 **WARNING:** Cancer - www.P65Warnings.ca.gov.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 3-0-0

HMIS: 3-0-0

Initial preparation date: 07/14/20

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 07.14.2020

Page 12 of 12

Skim Floor

Version #: 1

Revision Date:

End of Safety Data Sheet